# Cylinder Magnetic Separator - SCXL Series used in flow tube

Available for powdery and flaky material, such as flour and bran Easy-cleaning structure to wipe off Fe particles conveniently and efficiently.

#### **Technical data**

Magnetic performance: 9'000Gs-12'000Gs Materials of housing and other parts: 304 stainless steel/316 stainless steel Surface finish: Sand blasting/Powder painting

#### PATENTED PRODUCT ZL 2011 1 0319437.8



Model No.	Inlet	Height
	Φ A mm	B mm
SCXL1515	150	210
SCXL1818	180	210
SCXL2020	200	210



OeMag Beijing OeMag International Co., Ltd

Tel: +86-10-67609550; Fax: +86-10-67609565; E-mail: oemag@oemag.com

# Positive pressure conveying

Available for powdery and flaky material, such as flour and bran Easy-cleaning structure to wipe off Fe particles conveniently and efficiently Available for positive pressure conveying

## **Technical data**

Magnetic performance: 10'000Gs Materials of housing and other parts: 304 stainless steel/316 stainless steel Surface finish: Sand blasting/Powder painting



Model No.	Capacity(t/h)	Inlet	Dimension	
		Φ A mm	$\Phi \mathrm{B}\mathrm{mm}$	C mm
SCXL1516H	11	150	150	210
SCXL1818H	16	180	180	210
SCXL2020H	20	200	200	210

OeMag



Beijing OeMag International Co., Ltd

Tel: +86-10-67609550; Fax: +86-10-67609565; E-mail: <u>oemag@oemag.com</u>

# Negative pressure conveying

Available for powdery and flaky material, such as flour and bran Easy-cleaning structure to wipe off Fe particles conveniently and efficiently Available for negative pressure conveying

### **Technical data**

Magnetic performance: 10'000Gs Materials of housing and other parts: 304 stainless steel/316 stainless steel Surface finish: Sand blasting/Powder painting





Model No.	Capacity(t/h)	Inlet	Dimension	
		$\Phi A mm$	$\Phi \mathrm{B}\mathrm{mm}$	C mm
SCXL1516G	11	150	150	210
SCXL1818G	16	180	180	210
SCXL2020G	20	200	200	210

OeMag



Beijing OeMag International Co., Ltd

Tel: +86-10-67609550; Fax: +86-10-67609565; E-mail: oemag@oemag.com